

ARC WELDERS ARC400HD (RA40HD)



Estimated Power &
Energy Savings -
35 to 55%

Estimated
Labour Savings -
60%

PRODUCT FEATURES / DESCRIPTION

- Arc -Force for Anti-Sticking.
- Hot - Start (0 - 130 A) to Start the Welding Arc Smoothly
- VRD Function ---Safe for Welders.
- Remote -Control Function Optional.
- Dust - Free Cooling System with Upgraded Duty Cycle.
- With Advanced TUBULAR IGBT Technology
- May Use With GENERATOR

APPLICATIONS:

- Education
- Maintenance, Repair
- Fabrication
- Ship Building /Installation
- Construction
- Pipe
- Foundries

TECHNICAL PARAMETERS

Power Voltage (V)	415 ± 15%, 3 ph, AC
Frequency (Hz)	50/60
Rated Input Current (A)	18
Rated Input Power Capacity (KVA)	13
No-load Voltage (V)	65 V
Current Adjust Range (A)	30 - 400
Efficiency	85%
Duty Cycle (%)	60
Power Factor	0.93
Protection class	IP21S
Electrode diameter (mm)	2.5 - 4
Weight (kg)	22
Overall dimension (mm)	415 × 262 × 468

* In view of continuous development RALLIWOLF reserves the right to modify / alter the design / modification without prior notice

Ralli Wolf Industries Ltd.

(Formerly Ralli Engineering Ltd)

An ISO 9001 : 2015 certified Organisation

Regd. Office : 4, Fairlie Place Kolkata - 700001 (India), E : info@ralliwolf.com, P : +91 33 2262 7341

SALES NETWORK : Ahmedabad | Akola | Baroda | Bangalore | Bhubaneswar | Bhopal | Chennai | Coimbatore | Cuttack | Delhi
Faridabad | Guwahati | Indore | Jaipur | Jamshedpur | Kolkata | Ludhiana | Mumbai | Nagpur | Pune | Raipur | Secunderabad | Trichy