



MIG SERIES



MMA



• Specifications

Products Type	MIG 400 IJ
Model	RM40N
Input Voltage (V)	AC 415 ± 15%
Frequency (HZ)	50/60
Rated Input Current (A)	21.1
Power (KVA)	15
Output Current Range (A)	50-400
MCHWC @ 60%	400A
MCAWC @ 100%	310A
Rated Output Voltage (V)	16.5-31.5
Duty Cycle (%)	60
Power Factor	0.93
Efficiency (%)	85
Wire-feeding Speed (m/min)	2.5-18
Wire Diameter	0.8/1.0/1.2
Output Cable (mm)	35+
MMA Facility	Available
Inverter Technology	IGBT
Type Wire Feeder	Separated
Net Weight (Kg)	28

• Features

- This inverter's stable arc is suitable for almost any welding need
 - Portable and Easy to Operate
 - Efficient and energy saving
 - Minimal spatter, deep penetration, beautiful welding seam
- With Advanced IGBT Technology

• Standard Accessories



* In view of continuous development RALLIWOLF reserves the right to modify / alter the design / modification without prior notice

Ralli Wolf Industries Ltd.

(Formerly Ralli Engineering Ltd)

An ISO 9001 : 2015 certified Organisation

Regd. Office : 4, Fairlie Place Kolkata - 700001 (India), E : info@ralliwolf.com, P : +91 33 2262 7341

SALES NETWORK : Ahmedabad | Akola | Baroda | Bangalore | Bhubaneswar | Bhopal | Chennai | Coimbatore | Cuttack | Delhi
Faridabad | Guwahati | Indore | Jaipur | Jamshedpur | Kolkata | Ludhiana | Mumbai | Nagpur | Pune | Raipur | Secunderabad | Trichy